

ROBE lighting s .r. o., Hazovice 2090 75661 Roznov pod Radhostem Czech Republic Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz

HolyPATT™

Add retro style to your next broadcast, corporate event, stage or film set with the latest edition to the PATT family, designed to give a classic warm tungsten glow with a twist of modern edge.



Light source

Tungsten LED bulb



Effects

496mm see through parabolic aluminium reflector with gold-brown coating



Again, taking inspiration from vintage broadcast luminaires, let the HolyPATT™ add gorgeous scenic elements to your show. With a timeless brushed aluminium finish, these fixtures are the perfect scenic element for set dressing or ambience.

Based on the PATT2013™, the larger HolyPATT™ features a 4W LED Vintage Soft Coil filament lamp with a colour temperature of 1.800 K to illuminate the see-through gold-brown parabolic reflector, producing a warm, atmospheric glow.

Silent in operation due to convection cooling, their ultra-smooth dimming makes them the ideal complement to any setting.

Let the HolyPATT™ add warmth and enhanced visual appeal to your life and sets!



ROBE lighting s .r. o., Hazovice 2090 75661 Roznov pod Radhostem Czech Republic Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz

Technical Specification

Source

• Light source type: Tungsten LED bulb

Base: E27

Recommended lamp type: Bell 60021 LED Vintage Soft Coil Filament 125mm Large Globe ES Cap 4W

Lifetime: 15.000 hours

• Colour temperature: 1.800 K

Optical system

• 496mm see through parabolic aluminium reflector with gold-brown coatin

Control and programming

• External Dimmer

Thermal specification

Maximum ambient temperature: 45°C (113°F)

Maximum surface temperature: 160°C (320°F)

Electrical specification and connections

Input voltage range: 120 V or 240 V, 50/60 Hz

Power consumption: 4 W

Approvals

• CE Compliant

• cETLus Compliant

Mechanical specification

• Height: 680 mm (26.77")

• Width: 695 mm (27.4")

Depth: 210 mm (8.26")

Weight: 7.2 kg (15.9 lbs)

Ingress protection rating: IP20



ROBE lighting s .r. o., Hazovice 2090 75661 Roznov pod Radhostem Czech Republic Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz

Rigging

- Mounting points: M12 mounting for clamp or spigot
- Universal operating position

Included items

- User Manual
- Power cord

Optional accessories

• Single Top Loader Case: 10120336

Dual Top Loader Case: 10120337

• Tripod: 10980374

Floor stand: 10980259

Spigot: 10980260

• Doughty Trigger Clamp: 17030386

• Safety wire 36 kg: 99011963

Lamp G125 E26: 14080096

• Lamp G125 E27: 14080093

Legal

- HolyPATT™ is a Trademark of Robe lighting s. r. o.
- HolyPATT™ is patented by Robe lighting s. r. o. and protected by one or more pending or issued patents